



OBOR2.E220579 Varnishes - Component

[Page Bottom](#)

Varnishes - Component

[See General Information for Varnishes - Component](#)**AEV LTD**

E220579

MARION ST

BIRKENHEAD, MERSEYSIDE CH41 6LT UNITED KINGDOM

Varnish Designation	ANSI Type	Thermal Class (°C)		
		Twisted Pair	Helical Coil	Curved Electrode
Aquameg 300	MW 35-C	180	-	-
Ultigard 618%	MW 35-C	180	-	-
Ultimeg 2000-372%, Ultimeg 2000-392%	MW 35-C	180	-	-
Ultimeg 2000-380	MW 16-C	220	180	-
	MW 28-C	130	130	-
	MW 30-C	180	180	-
	MW 35-C	180	180	-
	MW 76-C	155	180	-
Ultimeg 2000-520	MW 35-C	180	-	-
Ultimeg 2000-520LV	MW 35-C	180	-	-
Ultimeg 2000-520MV	MW 35-C	180	-	-
Ultimeg 2002#	MW 35-C	180	-	-
Ultimeg 2220#	MW 16-C	220	-	-

- May include one to three letter suffix to denote viscosity.

% - A suffix of one or two letter(s) combination indicating the color.

Marking: Company name and model designation.

[Last Updated](#) on 2015-05-06[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".